



48V 50ah LiFePO4 Rackmount Lithium Battery For Residential Commercial

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: XWELL
- Certification: UN38.3, MSDS, UL, CB, BIS, PSE, GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE
- Model Number: XW-5120W-1
- Minimum Order Quantity: 1 pcs
- Packaging Details: Carton
- Delivery Time: 7-10 working days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 pcs per month



Product Specification

- Full Voltage: 48V To 51.2V
- Cell Type: LiFePO4 Prismatic Battery
- Full Capacity: 50Ah 100Ah 200Ah
- Full Energy: 2.56Kwh 5.12Kwh 10.24Kwh (Optional)
- Discharge Current: 50A
- Max Charge Current: 50A
- Discharge Cut-off Voltage: 42.5V
- Display: LCD Optional
- Communication Interface: RS485, RS232, CAN
- Cycle Life: >6000 Cycles(80%DOD)
- Highlight: **LiFePO4 Rackmount Lithium Battery, Residential Rackmount Lithium Battery, Commercial rack mount 48v battery**

for more products please visit us on esslithiumbattery.com

Product Description

48V 50ah Batteries Residential Commercial Solar Energy 5u Rackmount LCD LiFePO4 51.2V 100ah 200ah Lithium Battery

Pack modular design, strong universality, convenient installation, simple operation, independent maintenance, high reliability, safety, large space, conducive to ventilation and heat dissipation, is the main component of household power supply, lithium iron phosphate battery has along life, enough stability, more security and other characteristics.

New grade A cylindrical battery cells, the discharge rate is higher than the prismatic cells. Between the cell and the cell is fixed with a bracket to dissipate heat, the effective heat dissipation area is more than 64 times that of the prismatic cells battery.


Features

1. Grade A cell, sort them to one grade (5mQ/2mV) before assembly, strictly control the consistency of cells
2. Smart BMS control the balance of series cells
3. Cells holder and pure corn connection strap to keep the stability of cells
4. Full cycle before shipping
5. Screw fastenings

Rackmount Lithium Battery Specification


Model	51.2V50Ah	51.2V100Ah	51.2V200Ah
Nominal voltage	51.2V		
Nominal capacity (kwh)	2.56	5.12	10.24
Cell type	LiFePO4		
Standard charge voltage	54.6V (adjustable)		
Max charge current	50A		
Discharge cut-off voltage	42.5V (adjustable)		
Max discharge current	50A		
Display	LCD (Optional)		
Communication interface	CAN/RS485/RS232		
Cycle life	>6000 Cycles (80%DOD)		
Charge temperature range	0~45°C		
Discharge temperature range	-20~60°C		
Color	Black		
Dimension (mm)	442x410x133 3U	442x410x177 4U	550x442x220 5U
Weight	About 35Kg	About 42Kg	About 84Kg
Installation method	Rack Mount		

Cell Specification of Rackmount Lithium Battery




#	Item	Parameter
A	Height	119±1.0 mm
B	Width	160±1.0 mm
C	Thickness	≤50 mm
D	Tab Distance	97±0.5 mm


Operation Panel of Rackmount Lithium Battery



Size of Rackmount Lithium Battery



Structure of Rackmount Lithium Battery



#	Item	Material
(1)	Case Cover	SPCC
(2)	Case Hanger	SPCC
(3)	Insulation Sheet	Ethoxyline
(4)	Bus-Bar	Aluminum Alloy
(5)	Battery Cell	LFP, Aluminum Shell
(6)	Module Side Plate	ABS / PC
(7)	Cell Binding Loop	Plastic Steel
(8)	Case Bottom	SPCC
(9)	Insulating Wiring Terminal	Bakelite
(10)	Side Plate Combination Board	SPCC
(11)	BMS	PCB
(12)	Commination Board	PCB
(13)	DC Switch	/
(14)	Handle	Sherardized SPCC
(15)	Case Front Cover	SPCC
(16)	Terminal Bar (+ & -)	/

Application of Rackmount Lithium Battery

Application Scenario



Data Center



C&I Park



Telecom Base



Medical Equipment

What We Offer?

Supply chain solution, strict quality control, real-time response
OEM/ODM Manufacturer, custom sizes and shapes available on request
Suggestion of new design or material, new technology and cost structure
Engineers team at your service
Flexible small orders are acceptable
One-stop supply to eliminating messy links



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.

+86 18620492985

sales@esslithiumbattery.com

esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China